

Compound Solution Pack

- [Overview](#)
- [Dependencies](#)
- [Downloads](#)
- [Installation](#)
- [Configuration](#)
- [Usage](#)
- [Display](#)
- [Correcting out-of-date child object relationships](#)
- [Content Models, Prescribed Datastreams and Forms](#)
- [Troubleshooting/Issues](#)

Overview

The Compound Solution pack module allows you to create what are called "compound objects." Compound objects function as "parent" objects that gather together one or more "child" objects. Child objects can be created with any other Islandora solution pack and have their own metadata. When you associate Islandora objects with a parent compound object, the parent-child relationship is recorded in the RELS-EXT structural metadata of the child objects (see bottom of page for sample RELS-EXT). Sequencing information can also be recorded in the RELS-EXT metadata so child objects can be displayed in their proper order. For example, a scanned postcard with a front and back view would have the following structure:

Parent object: Postcard Object (the compound object)

- Child object: Scan of postcard front (large image object) - Order 1 of 2
- Child object: Scan of postcard back (large image object) - Order 2 of 2

The "Compound" management tab allows for the addition, removal, and reordering of child objects from the parent compound object. Configuration options for the module are available through the Compound objects administrative menu ([admin/islandora/solution_pack_config/compound_object](#))

Dependencies

This module requires the following modules/libraries:

- [Islandora](#)

This module has the following as optional requirements for certain features:

For Islandora Compound Object JAIL Display:

- [JAIL](#) library
 - If utilizing the lazy loading image ability of the solution pack, enable the "Islandora Compound Object JAIL Display" block and ensure the JAIL library is present within `sites/all/libraries/JAIL`.

Downloads

[Release Notes and Downloads](#)

Installation

Install as usual, see [this](#) for further information.

Enable the Islandora compound object module (`admin/modules`). There are two block options for displaying compound objects within Islandora. Select one of the following:

- The first is the default "Islandora Compound Object Navigation" block. Go to `admin/structure/block/manage/islandora_compound_object/compound_navigation/configure` to find navigation controls and load all objects related to the parent compound.
- The second is the "Islandora Compound Object JAIL Display" block. Go to `admin/structure/block/manage/islandora_compound_object/compound_jail_display/configure` to use the [JAIL](#) library, which allows for lazy loading of images. This allows the block to load images only when they are being accessed which will greatly increase performance on compounds with many children.

If utilizing the lazy loading image ability of the solution pack, the [JAIL](#) library must be present within `sites/all/libraries/JAIL`.

Configuration

Set the 'Child relationship predicate' and 'Solr filter query', as well as select options in Administration » Islandora » Solution pack configuration » Compound Object Solution Pack ([admin/islandora/solution_pack_config/compound_object](#)).

1. **Only allow compound objects to have child objects associated with them.**
 - Checked: you can only add child objects to Islandora objects with the "Compound Solution Pack" type. [With this option checked, whenever you delete a Compound Object, Islandora will not delete the child object(s). It only removes the relationship predicate from the child objects.]
 - Unchecked: all objects can have child objects. [Caution: If you uncheck this option, you run the risk of having orphan child objects if you ever delete a "parent" object that does not use the compoundCModel Content Model. This is because Islandora does not remove the relationship predicates from child objects if the parent wasn't a real "Compound Object."]
2. **Generate a thumbnail for compound objects from their first child.**
 - Checked: A thumbnail will be generated and attached to the compound object as a TN datastream.
 - Unchecked: No thumbnail is generated and a system default thumbnail will display.
3. **Hide child objects in RI results**
 - Checked: Child objects will not be displayed in the Islandora browse. Only parent objects will display.
 - Unchecked: Child objects and parent objects will be displayed in the Islandora browse.
4. **Hide child objects in Solr results**
 - a. Checked: Child objects will not be displayed in Solr search results. Only parent objects will display.
 - b. Unchecked: Child objects and parent objects will be displayed in the Islandora search.
5. **Solr Filter Query**
 - This is the query that enables the "Hide child objects in Solr results" function. The default value is ``-RELS_EXT_isConstituentOf_uri_mt: [* TO *]``
6. **Child relationship predicate**
 - This is the statement in the RELS-EXT metadata that associates child objects with parent objects. The default value is ``isConstituentOf``
7. **Use alternative, autoloading display for compounds?**
 - Checked: Enables the JAIL display (dependencies and blocks also need to be configured. See the documentation for "Installation" and "Display" for more information.)
 - Unchecked: The default display will be used.
8. **Display compound object parents in the breadcrumbs on children objects**
 - Checked: The parent object will appear in the breadcrumb navigation.
 - Unchecked: The parent object will not appear in the breadcrumb navigation.
9. **Compound Member Query**
 - (Default) Legacy SPARQL - Does a SPARQL query followed by an access check.
 - SPARQL - Does a SPARQL query with filters. Generally faster than the default option.

Optionally, enable the JAIL compound block to utilize the lazy loading image ability as outlined below.

Only allow compound objects to have child objects associated with them

If unchecked, all objects may have child objects.

Generate a thumbnail for compound objects from their first child

If checked, the thumbnail for a compound object will be generated from its first child object.

Hide child objects in RI results

If checked, child objects will be hidden. Only visible within the compound context.

Hide child objects in Solr results

If checked, child objects will be hidden. Only visible within the compound context.

Solr filter query *

Filter compound object children from Solr results.

Child relationship predicate *

Changing this after objects have been created will break functionality. Should be part of info:fedora/fedora-system:def/relations-external#

Use alternative, autoloading display for compounds?

Requires [JAIL](#) library to be present.

Use derivative hooks for parent thumbnail updates?

Changes to the TN datastream of a compounds first child will be reflected on the parent.

Display compound object parents in the breadcrumbs on children objects.

Redirect to first child when a compound object is requested.

Users will be redirected to the first child of a Compound Object when enabling this setting.

Compound Member Query

(Default) Legacy SPARQL – Does a SPARQL query followed by an access check.

SPARQL – Does a SPARQL query with filters. Generally faster than the default option.

Select the method that will be used to find the children of the compound objects.

Save configuration

Usage

To create a compound object:

1. Go to parent collection.
2. Click "Manage".
3. Enable the "Compound Object" object under "Collection" tab, then click "Update Collection Policy".
4. After adding compound objects to your Collection Policy, you will be able to click the "Overview" tab and "Add an Object".
5. Select "Islandora Compound Object Content Model" then "Next".
6. Select your metadata form, such as the "Compound Object MODS form", then "Next". [If prompted for a MARCXML file, choose that file if you have one. If you do not have one, just click "Next."]
7. Fill in your metadata form then click "Next".
 - Compound objects do not have content datastreams. This process creates a "parent" compound object that child objects can be associated with. The content is attached to the child objects.
8. After the compound object has been created, go to "Manage" > "Compound" to associate objects with the parent compound object.
 - Child objects must already exist in your repository before you can add them.
9. Under the "Add Child Object" field, enter the PID for each object to be added to the compound object.
 - Child objects can only be added one at a time. The "Child Object Pid/Label" box has an autocomplete function that searches for objects by label or PID.
10. Click "Save" when all the child objects are associated with the parent objects.

Once a child has been added to the compound, the view of the compound will use the metadata and thumbnail from the first object to render the main object view. To reorder objects, go to the parent object's Manage tab, select "Compound", and use the "Reorder" list. If you do reorder the child objects, be sure to click "Save changes" in the "Reorder" fieldset.

Child objects can be removed from parent objects from the parent object Manage >Compound tab. This removes the association from the RELS-EXT metadata but does not remove the child object from the repository.

Display

The object view of a compound object is replaced by the view of its first child object. After a compound object is created, the "Islandora Compound Object Navigation" block must be activated and set in an appropriate region. When a user navigates to a compound object, this block will render a thumbnail view of all the additional objects linked via the compound object.

Block options

There are two block options for displaying compound objects within Islandora. The default "Islandora Compound Object Navigation" block will provide navigation controls and loading of all objects related to the parent compound. The other option "Islandora Compound Object JAIL Display," is a block utilizing the [JAIL](#) library which allows for "lazy loading" of images. This allows the block to load images only when they are being accessed, which will greatly increase performance on compound objects with many children. See the "Installation" section for more information about the two display options.

Sidebar second		
 Islandora Compound Object JAIL Display	Sidebar second ▼	configure
 Islandora Compound Object Navigation	Sidebar second ▼	configure

Theme

The "Islandora Compound Object Navigation" block can be themed. Use the hook: `theme_islandora_compound_prev_next()`.

Correcting out-of-date child object relationships

Previous versions of this module (Islandora 7.x-1.2 and earlier) had a different predicate in the RELS-EXT to associate child objects with parent objects. To update to the new compound object predicate, run the drush command ``update_rels_predicate`` from the command line. This will update the predicates of existing compound objects to ``isConstituentOf``. This command accepts no arguments.

Content Models, Prescribed Datastreams and Forms

The Compound Solution Pack comes with the following Content Models:

- Islandora Compound Object Content Model (islandora:compoundCModel)
- Compound Collection (islandora:compound_collection)

A parent object created using the Compound Solution Pack's compoundCModel will have the following datastreams:

RELS-EXT	Default Fedora relationship metadata
MODS	MODS record, created at time of ingest
DC	Dublin Core record
TN	Thumbnail image, created at time of ingest

The Compound Solution Pack comes with the "Compound Object MODS form" for editing the MODS datastream (admin/islandora/xmlform).

Sample RELS-EXT for Parent Object (Compound Object)

```
<rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#" xmlns:fedora="info:fedora/fedora-system:def/relations-external#"
xmlns:fedora-model="info:fedora/fedora-system:def/model#" xmlns:islandora="http://islandora.ca/ontology/relsext#">
  <rdf:Description rdf:about="info:fedora/islandora:3">
    <fedora:isMemberOfCollection rdf:resource="info:fedora/islandora:compound_collection"></fedora:isMemberOfCollection>
    <fedora-model:hasModel rdf:resource="info:fedora/islandora:compoundCModel"></fedora-model:hasModel>
  </rdf:Description>
</rdf:RDF>
```

Sample RELS-EXT for Child Object (Large Image Object)

```
<rdf:RDF xmlns:fedora="info:fedora/fedora-system:def/relations-external#" xmlns:fedora-model="info:fedora/fedora-system:def/model#"
xmlns:islandora="http://islandora.ca/ontology/relext#" xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#">
  <rdf:Description rdf:about="info:fedora/islandora:2">
    <fedora:isMemberOfCollection rdf:resource="info:fedora/islandora:sp_large_image_collection"></fedora:
isMemberOfCollection>
    <fedora-model:hasModel rdf:resource="info:fedora/islandora:sp_large_image_cmodel"></fedora-model:hasModel>
    <fedora:isConstituentOf rdf:resource="info:fedora/islandora:3"></fedora:isConstituentOf>
    <islandora:isSequenceNumberOfislandora_3>1</islandora:isSequenceNumberOfislandora_3>
  </rdf:Description>
</rdf:RDF>
```

Troubleshooting/Issues

Having problems or solved a problem? Check out the Islandora google groups for a solution.

- [Islandora Group](#)
- [Islandora Dev Group](#)