Configure ProQuest Access

Purpose

This page describes how to configure access to ProQuest in Circulation Manager.

Prerequisites

- 1. Ensure that the organisation that wants to use ProQuest as a vendor can authenticate its patrons using SAML.
- 2. Ensure that the organisation's IdP can send back to Circulation Manager a unique patron D as a SAML attribute.
- 3. Ensure that you have machines with static IP addresses that ProQuest can whitelist.

Configuring Circulation Manager

Configuration settings

The table below contains a description of different ProQuest integration's configuration settings:

Parameter	Mandatory	Default	Description	
Data source name	Yes	ProQuest	The name of the Circulation Manager's data source used to store information about ProQuest books.	
BooksCatalo g Service's URL	Yes		The URL of BooksCatalog service used to download the ProQuest OPDS 2.0 feed and described on ProQuest API page. Please note that the BooksCatalog service is accessible only from whitelisted IP addresses. Please refer to ProQuest API for more information.	
PartnerAuthT oken Service's URL	Yes		The URL of PartnerAuthToken service used to create a ProQuest JWT bearer token required to authenticate in other ProQuest services. and described on ProQuest API page	
DownloadLin k Service's URL	Yes		The URL of DownloadLink service used to download ProQuest books and described on ProQuest API page.	
ProQuest JWT token's expiration timeout	No	3600	Determines how long in seconds can a ProQuest JWT token be valid.	
List of SAML attributes containing an affiliation ID	No	eduPerso nPrincipal Name, eduPerso nScopedA ffiliation	ProQuest integration assumes that the SAML provider is used for authentication. ProQuest JWT bearer tokens required by the most ProQuest API services are created based on the affiliation ID - SAML attribute uniquely identifying the patron. This setting determines what attributes the ProQuest integration will use to look for affiliation IDs. The ProQuest integration will investigate the specified attributes sequentially and will take the first non-empty value.	
Test SAML affiliation ID	No	1	This configuration setting is really useful for testing ProQuest API without setting up a SAML authentication provider. If this configuration setting is set, then the ProQuest integration will be using its value in the case when it cannot find a SAML affiliation ID. Please contact ProQuest before using it.	
Default audience	No		If ProQuest does not specify the target audience for their books, assume the books have this target audience.	
Feed page's size	No	5,000	This value determines how many publications will be on a single page fetched from the BooksCatalog service. Please note that this value also affects how many publications will be committed in a single database transaction by Circulation Manager. Making this value too big may lead to different database issues.	
HTTP proxy's URL	No		URL of the proxy handling HTTP traffic. Proxies can be used for testing when trying to access ProQuest API from machines having non-whitelisted IP addresses. Please find more information below.	
HTTPS proxy's URL	No		URL of the proxy handling HTTPS traffic. Proxies can be used for testing when trying to access ProQuest API from machines having non-whitelisted IP addresses. Please find more information below.	

Proxies

As it was mentioned above it might be useful to use a proxy to test the SAML integration from the local machine which has an IP address non whitelisted by ProQuest. To do so you need to use a SOCKS proxy:

ssh -D 8888 -f -C -q -N <FQDN or IP address of the machine with a whitelisted IP address>

```
After you activated a SOCKS proxy, you'll need to create an HTTP proxy based on it:
```

```
npm install -g http-proxy-to-socks
hpts -s 127.0.0.1:8888 -p 8080
```

After this, you can use the following values for proxy settings:

- HTTP proxy's URL = http://localhost:8080
- HTTPS proxy's URL = https://localhost:8080

Depending on your system configuration you might face a weird SSL: WRONG_VERSION_NUMBER error. In this case you can try to use a SOCKS proxy:

• HTTPS proxy's URL = socks5://localhost:8888

Creating a ProQuest collection in Circulation Manager

- 1. Create a new collection with ProQuest protocol.
- 2. Set up all the mandatory configuration settings mentioned in the table above:

Libraries Admins Collections Admin Authentication Patron Authentication Stewide Settings Logging Metadata Analytics ColN Search Storage Discovery Uit of the BooksCatalog service's URL Required Uit of the PartnerAuthToken service's URL Required		Not Secure — cm.hilbertteam.net Č	Ê Ø _H
Admins Collections Admin Authentication Patron Authentication Sitewide Settings Logging Metadata Analytics CDN Search Storage External Catalogs Discovery URL of the BooksCatalog service's URL Required PartureAuthToken service's URL Required URL of the PortureAuthToken service's URL Required	Libraries		
Collections Admin Authentication Patron Authentication Sitewide Settings Logging Metadata Analytics CDN Search Storage External Catalogs Discovery URL of the BooksCatalog service's URL Required URL of the PartnerAuthToken service's URL Required	Admins	Collection configuration	
Admin Authentication Patron Authentication Sitewide Settings Logging Metadata Metadata Analytics CDN Search Storage External Catalogs Discovery URL of the BocksCatalog service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	Collections	Edit ProQuest	
Petron Authentication Required Fields Sitewide Settings Name Required Logging ProQuest Metadata Protocol Analytics ProQuest • CDN Data source name Required Search ProQuest Storage ProQuest External Catalogs URL of the BooksCatalog service's URL Required Discovery URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required URL of the PartnerAuthToken service's URL Required	Admin Authentication		
Sitewide Settings Name Required Logging ProQuest Metadata ProQuest Analytics ProQuest CDN Data source name Required Search ProQuest Storage ProQuest External Catalogs URL of the BooksCatalog service's URL Required Discovery URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	Patron Authentication	Required Fields	
Logging ProQuest Metadata ProQuest Analytics ProQuest CDN Data source name Required Search ProQuest Storage ProQuest External Catalogs URL of the BooksCatalog service's URL Required Discovery URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	Sitewide Settings	Name Peruired	
Metadata Protocol Analytics ProQuest CDN Data source name Required Search ProQuest Storage ProQuest External Catalogs URL of the BooksCatalog service's URL Required Discovery URL of the BooksCatalog service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	Logging	ProQuest	
Analytics ProQuest CDN Data source name Required Search ProQuest Storage ProQuest associated with this collection. BooksCatalog service's URL Required URL of the BooksCatalog service's URL Required URL of the BooksCatalog service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required DownloadLink service's URL Required	Metadata	Protocol	
Import books from a ProQuest OPDS 2.0 feed. Search Data source name Required Storage ProQuest External Catalogs Name of the data source associated with this collection. Discovery URL of the BooksCatalog service endpoint. PartnerAuthToken service's URL Required URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required URL of the PartnerAuthToken service suppoint.	Analytics	ProQuest 🔶	
Search ProQuest Storage ProQuest External Catalogs BooksCatalog service's URL Required Discovery URL of the BooksCatalog service endpoint. PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	CDN	Import books from a ProQuest OPDS 2.0 feed.	
Storage Name of the data source associated with this collection. External Catalogs BooksCatalog service's URL Required Discovery URL of the BooksCatalog service endpoint. PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required URL of the PartnerAuthToken service's URL Required	Search	ProQuest	
BooksCatalog service's URL Required Discovery BooksCatalog service endpoint PartnerAuthToken service's URL Required URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required	Storage	Name of the data source associated with this collection.	
Discovery URL of the BooksCatalog service endpoint PartnerAuthToken service's URL Required URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required	External Catalogs	BooksCatalog service's URL Required	
PartnerAuthToken service's URL Required URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required	Discovery	URL of the BooksCatalog service endpoint	
URL of the PartnerAuthToken service endpoint. DownloadLink service's URL Required	Discovery	PartnerAuthToken service's URL Required	
DownloadLink service's URL Required		URL of the PartnerAuthToken service endpoint.	
		DownloadLink service's URL Required	
URL of the DownloadLink service endpoint.		URL of the DownloadLink service endpoint.	

3. Set up optional configuration settings if required:

Optional Fields	/
ProQuest JWT token's ex	piration timeout
3600	
(Optional) Determines how long i	n seconds can a ProQuest JWT token be valid.
List of SAML attributes co	ntaining an affiliation ID
ProQuest integration assumes the bearer tokens required by the mo - SAML attribute uniquely identify ProQuest integration will use to lo the specified attributes sequentia	It the SAML provider is used for authentication. ProQuest JWT at ProQuest API services are created based on the affiliation ID ing the patron. This setting determines what attributes the ok for affiliation IDs. The ProQuest integration will investigate Ily and will take the first non-empty value.
eduPersonPrincipalName	Delete 🗑
eduPersonScopedAffiliati	Delete 🕯
uid 🗘	Add
Test SAML affiliation ID	
1	
(Optional) Test SAML affiliation ID using it.	used for testing ProQuest API. Please contact ProQuest befor
Default audience	
Adult	\$
If ProQuest does not specify the target audience.	arget audience for their books, assume the books have this
Feed page's size	
5000	

ProQuest Import Monitor

Please note that the import of ProQuest collections is done on a scheduled basis, the same way it's done for OPDS 1.x/OPDS 2.x collections.

However, the ProQuest import process is a very computationally expensive operation due to the inefficient ProQuest feed's internal structure and **proquest** _**import_monitor** is set up to run only twice a week:

- Tuesday 2 AM EST (Monday 11 PM PST).
- Friday 2 AM EST (Thursday 11 PM PST). This run uses an additional --process-removals flag which forces proquest_import_monitor to remove from Circulation Manager's catalog items that are no longer present in the ProQuest feed (it's not enabled by default).

The schedule above is subject to change.