

Islandora Solr Metadata

Overview

The **Islandora Solr Metadata** module provides an interface to construct displays of Solr indexed metadata from one or more schemas on the Islandora objects.

Dependencies

This module requires the following modules/libraries:

- Islandora Core Module
- APPENDIX G - All About Tuque
- Islandora Solr Search

Downloads

[Release Notes and Downloads](#)

Code Repository

https://github.com/islandora/islandora_solr_metadata

Installation

Install as usual, see this for further information.

Configuration

To use Solr indexed metadata in the display, go to Administration > Islandora > Metadata Display ([admin/islandora/metadata](#)) and select "Islandora Solr Metadata" to be the default display viewer. Click **Save Configuration**.

[blocked URL](#)

To set up a display, go to Administration > Islandora > Solr Index » Metadata Display ([admin/islandora/search/islandora_solr/metadata](#)).

[blocked URL](#)

Create a custom display

1. In the **Metadata Display** tab, select the **Field Configuration** tab.
2. Enter a configuration name (this will only be displayed to administrators.)
3. Create a machine name for this custom display (this can be the same as the configuration name).
4. Click **Add Configuration**.

Add metadata fields and labels to a custom display

1. After you have created a custom display, click the linked configuration name to add fields to that display.
2. Select the content models that will use this display.
3. Click on the new display to add fields.

[blocked URL](#)

4. Add fields to the display by entering **APPENDIX D - SOLR SCHEMA (SEARCH) Term Reference** with type "string." As you type in the "Add Field" box, field names will be suggested from the index. Once a field is selected, click "Add". In order to edit the field, click **Save Configuration** at the bottom of the form.

[blocked URL](#)

5. After you add fields, you can create custom labels, choose whether to hyperlink the field values in the display, or apply truncation options by clicking the edit button next to the field. The edit button appears only after you click Save Configuration at the bottom of the form. By default, the display label will be the Solr field name. A hyperlinked field value will launch a new Solr search for other records with that same value.

[blocked URL](#)

6. Truncation can also be applied from the **edit** menu. Truncation can be applied to separate values or an entire field. You can specify the maximum field length (use 0 or less to disable truncation), and choose whether to attempt truncation on a word boundary and whether or not to append an ellipsis to the end of a field when it is begin truncated.

[blocked URL](#)

7. The "Description" field that shows up directly under an object's viewing derivative is configured separately from the other display fields. Enter the field and an optional label in the Description settings.

[blocked URL](#)

6. Click **Save Configuration**.

Content models with multiple metadata displays

A content model can have more than one metadata display configuration associated with it. In this case, all fields present in both configurations are displayed, and the order of fields is determined by Solr field weightings.

Notes

- To use Solr Metadata with Scholar's citation/thesis cModels, please enable the **'Use Standard Metadata Display'** option in Administration >> Islandora >> Solution pack configuration >> Scholar (/admin/islandora/solution_pack_config/scholar).

[blocked URL](#)